



INTERIOR ACOUSTICS MATERIAL SAFETY DATASHEET

PRODUCT DESCRIPTION

All Autex Interior Acoustic products are made from 100% polyester fibres with no chemical binders and certified low VOC. Available in a range of wall coverings, panels and ceiling systems. Autex Interior Acoustics are light weight, easy to install and are suitable for new builds and retrofits.

PRODUCT NAMES

- Etch™
- Symphony™
- Workstation™
- Cube™
- Composition®
- Composition® Peel'n'Stick Tiles
- Quietspace® Frontier™
- Quietspace® Horizon
- Quietspace® 3D Tiles
- Quietspace® Ceiling Tiles
- Quietspace® 3D Ceiling Tiles
- Quietspace® Panel
- Quietspace® Lattice
- Quietspace® Accent Ceiling Tile

PHYSICAL DESCRIPTION

Chemical Entity: Polyester Fibre from PET (Polyethylene Terephthalate)

Odour:	No odour
pH:	7.8 (pH 7 being neutral)
Boiling Point:	N/A
Melting Point	250°C
Max. Recommended Service Temp:	80°C
Vapour Pressure	N/A
Specific Gravity	Polyester 1.38
Flash Point	N/A
Explosive Limits	N/A
Solubility in Water	Not soluble
Moisture Absorption	Less than 0.03% by weight
Relative Vapour Density	N/A
Percent Volatiles	Nil
Corrosiveness	Non-corrosive

STORAGE AND TRANSPORT

Packaging as recommended by the manufacturer. Top stow and keep clean and dry. Do not squash or bend product or packaging.

MOISTURE ABSORPTION

The structural integrity of Autex Interior Acoustic products will not be affected by moisture. Exposure of polyester fibre to an atmosphere of 50°C at 90% relative humidity for four days showed moisture absorption by weight of less than 0.03%.

EXTINGUISHING MEDIA

Water spray of fog, foam, dry chemical and carbon dioxide. Material will shrink from flame and may drip.

HAZARDS IDENTIFICATION

Autex Interior Acoustic products are non-hazardous and non-dangerous goods.

HEALTH EFFECTS/ PERSONAL PROTECTION

There are no known hazards relating to the use or handling of Autex Interior Acoustic products. No protective clothing or gloves are required when handling or installing Autex Interior Acoustic products. There is no dust content in the products and any free fibres which may be present are not of respirable size.

ZERO ODP

Autex Interior Acoustic products manufactured from 100% polyester have an Ozone Depleting Potential (ODP) of zero, meaning no ozone depleting substances are present in the product or used in direct manufacture of the product. For a full list of International Ozone Depleting Potential, please refer to the declaration on our website www.autex.com.au.





INTERIOR ACOUSTICS MATERIAL SAFETY DATASHEET

FIRE RATINGS

Autex Interior Acoustics is self extinguishing.

All Autex Interior Acoustics products conform to the requirements of the Building Code of Australia (NCC) requirements as tested under AS1530.3 and ISO 9705.

AS ISO 9705-2003

Australian Group Number: Group 1

SMOGRARC: Less than 100m²/s²

Tested in accordance with AS5637.1:5015

as required by BCA C1.10

Issued 11th March 2013, BRANZ (FAR 4045)

(FI 5550 for e-foil ARD)

AS1530.3

Ignability Index (0-20) 0

Heat Evolved Index (0-10) 0

Spread of Flame Index (0-10) 0

Smoke Developed Index (0-10) 3

APL Report 98055

IEC 60695-11-5

(Downlight Fire Test Standard)

Autex Interior Acoustic products has been tested and certified non-flammable and complies with the fire requirements of IEC 60695-11-5.

INDOOR ENVIRONMENTAL QUALITY (IEQ)/VOC EMISSIONS

Autex polyester exceeds the current leading world standards established by 'Good Environmental Choice Australia' (GECA) and the Green Guard Environmental Institute.

Green Guard VOC standards are the recommended maximum exposure for airborne volatile organic chemical levels established by the US National Toxicology Program (NTP), the International Association for Research on Cancer (IARC) and the World Health Organisation (WHO).

Autex Interior Acoustic polyester has been tested by Cetec Pty Ltd (Report: RCV080408) for chemical emissions as follows:

VOC concentration: 0.01 mg/m³ (7days)

GECA/Green Guard Limit: 0.25mg/m³ (7days)

ENVIRONMENTAL

Autex Interior Acoustic products are manufactured using 100% polyester fibre and contain a minimum of 50% post-consumer recycled content (i.e. PET plastic bottles).

Autex Interior Acoustic products are Global GreenTag Green Rate Level A certified. Autex Interior Acoustic products are also Declare certified to be Red-List Free and can be used in Living Building Challenge projects.

All Autex product declarations are independently verified under the auditing process of our ISO 14001 Environmental Management System. For more information, please contact your Autex Representative or visit our website www.autex.com.au.

Autex Pty Ltd

166 Bamfield Road
PO Box 5099
West Heidelberg, Melbourne
VIC 3081, Australia

Phone **+61 3 9457 6700**

Fax **+61 3 9457 1020**

Freephone **1800 678 160**

www.autex.com.au

Autex Pty - WA

195 Bank St
East Victoria Park
Perth, WA 6101

Phone **+61 8 9355 1911**

Fax **+61 8 9355 1032**

Autex Pty - NSW

16 Bushells Place
Wetherill Park
Sydney, NSW 2164

Phone **+61 8 9355 1911**

Fax **+61 8 9355 1032**

Autex Pty - QLD

7-11 Lancashire
Acacia Ridge
Brisbane, QLD 4110

Phone **+61 8 9355 1911**

Fax **+61 8 9355 1032**

*If you live outside of these states, please contact our head office in Melbourne, Victoria.

AUG 2017

AN ISO 9001 AND ISO 14001 CERTIFIED COMPANY